# SAFETY DATA SHEET

#### 1. Identification

Product identifier SILVER GRAY 325029 - ROOF FLASHING PAINT

Other means of identification

Product code 325029

Recommended use Roof flashing paint Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ROOFMASTER PRODUCTS COMPANY

Address 750 MONTEREY PASS ROAD

MONTEREY PARK, CA 91754-3607

**United States** 

**Telephone** 1(323) 261-5122 **E-mail** Not available.

Emergency phone number 1(800) 255-3924 [Chem-Tel]

# 2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsAcute toxicity, oralCategory 4Acute toxicity, dermalCategory 4Serious eye damage/eye irritationCategory 2AGerm cell mutagenicityCategory 1BCarcinogenicityCategory 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol. Harmful if swallowed. Harmful in contact with skin. Causes serious eye irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If

inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. If eye irritation persists: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

98.52% of the mixture consists of component(s) of unknown acute oral toxicity. 99.98% of the mixture consists of component(s) of unknown acute dermal toxicity.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ACETONE		67-64-1	30-45
ALUMINUM		7429-90-5	20-35
BUTANE		106-97-8	10-25
PETROLEUM NAPHTHA		64742-48-9	10-25
PROPANE		74-98-6	10-25
AMORPHOUS SILICA		63231-67-4	<10
n-BUTYL ALCOHOL		71-36-3	<10

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Rinse skin with water/shower. Get medical advice/attention if you feel unwell. Get medical attention

if irritation develops and persists. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Iost important May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Most important symptoms/effects, acute and delayed

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Ingestion

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

### 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Powder. Alcohol resistant foam. Dry sand. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire. Carbon dioxide (CO2).

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

**General fire hazards** Extremely flammable aerosol.

Material name: SILVER GRAY 325029 - ROOF FLASHING PAINT 325029 Version #: 02 Revision date: 06-12-2016 Issue date: 06-09-2016

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

#### **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

U.S. OSHA Table 7-1 Limits for Air Contaminants (29 CFR 1910.1000)

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

Occupational exposure limits

ACETONE (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
ALUMINUM (CAS (429-90-5)	PEL	5 mg/m3	Respirable dust.
•		15 mg/m3	Total dust.
-BUTYL ALCOHOL (CAS 11-36-3)	PEL	300 mg/m3	
,		100 ppm	
PETROLEUM NAPHTHA CAS 64742-48-9)	PEL	400 mg/m3	
,		100 ppm	
PROPANE (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
JS. OSHA Table Z-3 (29 CFR 1910.1000)			
Components	Туре	Value	
MORPHOUS SILICA CAS 63231-67-4)	TWA	0.8 mg/m3	
		20 mppcf	
JS. ACGIH Threshold Limit Values			
Components	Type	Value	Form
ACETONE (CAS 67-64-1)	STEL	750 ppm	

Material name: SILVER GRAY 325029 - ROOF FLASHING PAINT

SDS US

**US. ACGIH Threshold Limit Values Form** Components Value Type ALUMINUM (CAS TWA 1 mg/m3 Respirable fraction. 7429-90-5) **STEL** BUTANE (CAS 106-97-8) 1000 ppm n-BUTYL ALCOHOL (CAS **TWA** 20 ppm 71-36-3)

#### **Biological limit values**

**ACGIH Biological Exposure Indices** 

Components	Value	Determinant	Specimen	Sampling Time
ACETONE (CAS 67-64-1)	50 mg/l	Acetone	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

US - California OELs: Skin designation

n-BUTYL ALCOHOL (CAS 71-36-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

n-BUTYL ALCOHOL (CAS 71-36-3) Skin designation applies.

US - Tennessee OELs: Skin designation

n-BUTYL ALCOHOL (CAS 71-36-3)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

n-BUTYL ALCOHOL (CAS 71-36-3)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Aerosol.
Color Silver. Grey.
Odor Solvent.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

-43.78 °F (-42.1 °C) estimated

Flash point -133.6 °F (-92.0 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits

Flammability limit - lower 1.9 % estimated

(%)

Material name: SILVER GRAY 325029 - ROOF FLASHING PAINT 325029 Version #: 02 Revision date: 06-12-2016 Issue date: 06-09-2016

Flammability limit - upper 12.8 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 2072.95 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 550 °F (287.78 °C) estimated

**Decomposition temperature**Not available. **Viscosity**Not available.

Other information

Density 6.69 lb/gal

Flammability class Flammable IA estimated

Percent volatile 79.82 %w/w

Specific gravity 0.8

**VOC (Weight %)** 339.58 g/l MATERIAL 547.5 g/l COATING

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materialsStrong oxidizing agents. Nitrates. Fluorine. Chlorine.Hazardous decompositionNo hazardous decomposition products are known.

products

# 11. Toxicological information

# Information on likely routes of exposure

**Inhalation** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful

Skin contactHarmful in contact with skin.Eye contactCauses serious eye irritation.

**Ingestion** Harmful if swallowed.

Symptoms related to the Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation.

physical, chemical and toxicological characteristics

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

# Information on toxicological effects

Acute toxicity Harmful in contact with skin. Harmful if swallowed. Narcotic effects.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

AMORPHOUS SILICA (CAS 63231-67-4)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** 

Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

# 12. Ecological information

**Ecotoxicity** 

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
ACETONE (CAS 67-6	64-1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
ALUMINUM (CAS 742	29-90-5)		
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.16 mg/l, 96 hours
n-BUTYL ALCOHOL (	(CAS 71-36-3)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1897 - 2072 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	100 - 500 mg/l, 96 hours
PETROLEUM NAPHT	ΓΗΑ (CAS 64742-4	8-9)	
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

**ACETONE** -0.24BUTANE 2.89 n-BUTYL ALCOHOL 0.88 **PROPANE** 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Material name: SILVER GRAY 325029 - ROOF FLASHING PAINT 325029 Version #: 02 Revision date: 06-12-2016 Issue date: 06-09-2016 Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

# 14. Transport information

DOT

**UN number** Not available.

UN proper shipping name Consumer commodity

Transport hazard class(es)

Class ORM-D Subsidiary risk -Label(s) None

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions Limited Quantity

Packaging exceptions156, 306Packaging non bulk156, 306Packaging bulkNone

**IATA** 

UN number ID8000

UN proper shipping name Consumer commodity

Transport hazard class(es)

Class 9
Subsidiary risk ORM-D
Packing group Not applicable.

Environmental hazards

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo Allowed.

aircraft

Cargo aircraft only Allowed.

**IMDG** 

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No. EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

Material name: SILVER GRAY 325029 - ROOF FLASHING PAINT 325029 Version #: 02 Revision date: 06-12-2016 Issue date: 06-09-2016



# 15. Regulatory information

**US** federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

ACETONE (CAS 67-64-1)

BUTANE (CAS 106-97-8)

n-BUTYL ALCOHOL (CAS 71-36-3)

Listed.

PROPANE (CAS 74-98-6)

Listed.

# SARA 304 Emergency release notification

Not regulated.

# OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

# SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

## SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
ALUMINUM	7429-90-5	20-35
n-BUTYL ALCOHOL	71-36-3	<10

# Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

BUTANE (CAS 106-97-8) PROPANE (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

# Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

ACETONE (CAS 67-64-1) 6533

## Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

ACETONE (CAS 67-64-1) 35 %WV

**DEA Exempt Chemical Mixtures Code Number** 

ACETONE (CAS 67-64-1) 6532

#### **US** state regulations

# **US - California Candidate Chemicals: Listed**

**ACETONE (CAS 67-64-1)** 

**BUTANE (CAS 106-97-8)** 

PETROLEUM NAPHTHA (CAS 64742-48-9)

# US - California Candidate Chemicals: Listed on initial list

ALUMINUM (CAS 7429-90-5)

# US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

## **US. Massachusetts RTK - Substance List**

ACETONE (CAS 67-64-1)

ALUMINUM (CAS 7429-90-5)

**BUTANE (CAS 106-97-8)** 

n-BUTYL ALCOHOL (CAS 71-36-3)

PETROLEUM NAPHTHA (CAS 64742-48-9)

PROPANE (CAS 74-98-6)

## US. New Jersey Worker and Community Right-to-Know Act

**ACETONE (CAS 67-64-1)** 

ALUMINUM (CAS 7429-90-5)

**BUTANE (CAS 106-97-8)** 

n-BUTYL ALCOHOL (CAS 71-36-3)

PETROLEUM NAPHTHA (CAS 64742-48-9)

PROPANE (CAS 74-98-6)

## US. Pennsylvania Worker and Community Right-to-Know Law

**ACETONE (CAS 67-64-1)** 

ALUMINUM (CAS 7429-90-5)

BUTANE (CAS 106-97-8)

n-BUTYL ALCOHOL (CAS 71-36-3)

PETROLEUM NAPHTHA (CAS 64742-48-9)

PROPANE (CAS 74-98-6)

#### **US. Rhode Island RTK**

**ACETONE (CAS 67-64-1)** 

ALUMINUM (CAS 7429-90-5)

**BUTANE (CAS 106-97-8)** 

n-BUTYL ALCOHOL (CAS 71-36-3)

PROPANE (CAS 74-98-6)

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

# US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE (CAS 71-43-2)

CRYSTALLINE QUARTZ SILICA (CAS 14808-60-7)

ETHYL BENZENE (CAS 100-41-4)

FORMALDEHYDE (CAS 50-00-0)

Listed: February 27, 1987

Listed: October 1, 1988

Listed: June 11, 2004

Listed: January 1, 1988

## US - California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997 TOLUENE (CAS 108-88-3) Listed: January 1, 1991

# US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

TOLUENE (CAS 108-88-3) Listed: August 7, 2009

# US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No

325029 Version #: 02 Revision date: 06-12-2016 Issue date: 06-09-2016

Country(s) or region Inventory name On inventory (yes/no)\*

New Zealand New Zealand Inventory No

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

 Issue date
 06-09-2016

 Revision date
 06-12-2016

Version # 02

HMIS® ratings Health: 2\*

Flammability: 4 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 4 Instability: 0

NFPA ratings



Disclaimer

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create any warranty, expressed or implied. It is the responsibility of the user to determine the applicability of this information and the suitability of the material or product for any particular purpose.

Material name: SILVER GRAY 325029 - ROOF FLASHING PAINT 325029 Version #: 02 Revision date: 06-12-2016 Issue date: 06-09-2016

No

No