

SAFETY DATA SHEET

1. Identification

Product identifier TILE RED 325045 - ROOF FLASHING PAINT

Other means of identification

Product code 325045

Recommended use Flashing paint

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ROOFMASTER PRODUCTS COMPANY

Address 750 MONTEREY PASS ROAD
MONTEREY PARK, CA 91754-3607
United States

Telephone 1(323) 261-5122

E-mail Not available.

Emergency phone number 1(800) 255-3924 [Chem-Tel]

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Acute toxicity, oral	Category 4
	Acute toxicity, dermal	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 2
	Reproductive toxicity (fertility, the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Harmful if swallowed. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause genetic defects. Suspected of causing cancer. Suspected of damaging the unborn child. Suspected of damaging fertility. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

85.06% of the mixture consists of component(s) of unknown acute oral toxicity. 92.1% of the mixture consists of component(s) of unknown acute dermal toxicity. 83.11% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 83.11% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ACETONE		67-64-1	30-45
BUTANE		106-97-8	10-25
PROPANE		74-98-6	10-25
ETHYL BENZENE		100-41-4	<10
IRON OXIDE		1309-37-1	<10
n-BUTYL ALCOHOL		71-36-3	<10
TALC		14807-96-6	<10
TOLUENE		108-88-3	<10
XYLENE		1330-20-7	<10
AROMATIC HYDROCARBON		64742-94-5	<1
TITANIUM DIOXIDE		13463-67-7	<1
ZINC OXIDE		1314-13-2	<1
ZINC PHOSPHATE		7779-90-0	<1

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Powder. Alcohol resistant foam. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.
6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Environmental precautions	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
ACETONE (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm	
AROMATIC HYDROCARBON (CAS 64742-94-5)	PEL	400 mg/m3	
ETHYL BENZENE (CAS 100-41-4)	PEL	100 ppm 435 mg/m3	
IRON OXIDE (CAS 1309-37-1)	PEL	100 ppm 10 mg/m3	Fume.
n-BUTYL ALCOHOL (CAS 71-36-3)	PEL	300 mg/m3	
PROPANE (CAS 74-98-6)	PEL	100 ppm 1800 mg/m3	
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	1000 ppm 15 mg/m3	Total dust.
XYLENE (CAS 1330-20-7)	PEL	435 mg/m3	
ZINC OXIDE (CAS 1314-13-2)	PEL	100 ppm 5 mg/m3	Fume.
		5 mg/m3 15 mg/m3	Respirable fraction. Total dust.

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
TOLUENE (CAS 108-88-3)	Ceiling TWA	300 ppm 200 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
TALC (CAS 14807-96-6)	TWA	0.3 mg/m3 0.1 mg/m3 20 mppcf 2.4 mppcf	Total dust. Respirable. Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ACETONE (CAS 67-64-1)	STEL TWA	750 ppm 500 ppm	
AROMATIC HYDROCARBON (CAS 64742-94-5)	TWA	200 mg/m3	Non-aerosol.
BUTANE (CAS 106-97-8)	STEL	1000 ppm	
ETHYL BENZENE (CAS 100-41-4)	TWA	20 ppm	
IRON OXIDE (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
n-BUTYL ALCOHOL (CAS 71-36-3)	TWA	20 ppm	
TALC (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	10 mg/m3	
TOLUENE (CAS 108-88-3)	TWA	20 ppm	
XYLENE (CAS 1330-20-7)	STEL TWA	150 ppm 100 ppm	
ZINC OXIDE (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.

**US. ACGIH Threshold Limit Values
Components**

Type

Value

Form

TWA

2 mg/m3

Respirable fraction.

Biological limit values

**ACGIH Biological Exposure Indices
Components Value**

Determinant

Specimen

Sampling Time

ACETONE (CAS 67-64-1) 50 mg/l

Acetone

Urine

*

ETHYL BENZENE (CAS 100-41-4) 0.15 g/g

Sum of
mandelic acid
and
phenylglyoxylic
acid

Creatinine in
urine

*

TOLUENE (CAS 108-88-3) 0.3 mg/g

o-Cresol, with
hydrolysis

Creatinine in
urine

*

0.03 mg/l

Toluene

Urine

*

0.02 mg/l

Toluene

Blood

*

XYLENE (CAS 1330-20-7) 1.5 g/g

Methylhippuric
acids

Creatinine in
urine

*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

n-BUTYL ALCOHOL (CAS 71-36-3)

Can be absorbed through the skin.

TOLUENE (CAS 108-88-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

n-BUTYL ALCOHOL (CAS 71-36-3)

Skin designation applies.

TOLUENE (CAS 108-88-3)

Skin designation applies.

US - Tennessee OELs: Skin designation

n-BUTYL ALCOHOL (CAS 71-36-3)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

AROMATIC HYDROCARBON (CAS 64742-94-5)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

n-BUTYL ALCOHOL (CAS 71-36-3)

Can be absorbed through the skin.

**Appropriate engineering
controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

**General hygiene
considerations**

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Aerosol.

Color

Red

Odor

Solvent.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point	Not available.
Initial boiling point and boiling range	-43.78 °F (-42.1 °C) estimated
Flash point	-133.6 °F (-92.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.3 % estimated
Flammability limit - upper (%)	12.8 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	2321 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	550 °F (287.78 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	6.59 lb/gal
Flammability class	Flammable IA estimated
Percent volatile	80.91 %w/w
Specific gravity	0.79
VOC (Weight %)	343.24 g/l MATERIAL 548.5 g/l COATING

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Harmful in contact with skin. Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Harmful if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity	Harmful in contact with skin. Harmful if swallowed. Narcotic effects.
-----------------------	---

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	May cause genetic defects.
Carcinogenicity	Suspected of causing cancer.
IARC Monographs. Overall Evaluation of Carcinogenicity	
ETHYL BENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
IRON OXIDE (CAS 1309-37-1)	3 Not classifiable as to carcinogenicity to humans.
TALC (CAS 14807-96-6)	2B Possibly carcinogenic to humans.
	3 Not classifiable as to carcinogenicity to humans.
TITANIUM DIOXIDE (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
TOLUENE (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
XYLENE (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
	Not listed.
US. National Toxicology Program (NTP) Report on Carcinogens	
	Not available.
Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility. Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species		Test Results
ACETONE (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
AROMATIC HYDROCARBON (CAS 64742-94-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours
ETHYL BENZENE (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours
		Fathead minnow (Pimephales promelas)	11.5 - 12.7 mg/l, 96 hours
n-BUTYL ALCOHOL (CAS 71-36-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1897 - 2072 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	100 - 500 mg/l, 96 hours

Components		Species	Test Results
TITANIUM DIOXIDE (CAS 13463-67-7)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours
TOLUENE (CAS 108-88-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	19.6 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	14.1 - 17.16 mg/l, 96 hours
XYLENE (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	10.464 - 16.114 mg/l, 96 hours 7.711 - 9.591 mg/l, 96 hours
ZINC OXIDE (CAS 1314-13-2)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	2246 mg/l, 96 hours
ZINC PHOSPHATE (CAS 7779-90-0)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.09 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

ACETONE	-0.24
BUTANE	2.89
ETHYL BENZENE	3.15
n-BUTYL ALCOHOL	0.88
PROPANE	2.36
TOLUENE	2.73
XYLENE	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	Not available.
UN proper shipping name	Consumer commodity

Transport hazard class(es)**Class** ORM-D**Subsidiary risk** -**Label(s)** None**Packing group** Not applicable.**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**Special provisions** Limited Quantity**Packaging exceptions** 156, 306**Packaging non bulk** 156, 306**Packaging bulk** None**IATA****UN number** ID8000**UN proper shipping name** Consumer commodity**Transport hazard class(es)****Class** 9**Subsidiary risk** ORM-D**Packing group** Not applicable.**Environmental hazards** No.**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**Other information****Passenger and cargo aircraft** Allowed.**Cargo aircraft only** Allowed.**IMDG****UN number** UN1950**UN proper shipping name** Aerosols, flammable**Transport hazard class(es)****Class** 2.1**Subsidiary risk** -**Label(s)** 2.1**Packing group** Not applicable.**Environmental hazards****Marine pollutant** No.**EmS** F-D, S-U**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.**IMDG****15. Regulatory information****US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
One or more components are not listed on TSCA.**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ACETONE (CAS 67-64-1)

Listed.

BUTANE (CAS 106-97-8)

Listed.

ETHYL BENZENE (CAS 100-41-4)	Listed.
n-BUTYL ALCOHOL (CAS 71-36-3)	Listed.
PROPANE (CAS 74-98-6)	Listed.
TOLUENE (CAS 108-88-3)	Listed.
XYLENE (CAS 1330-20-7)	Listed.
ZINC OXIDE (CAS 1314-13-2)	Listed.
ZINC PHOSPHATE (CAS 7779-90-0)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
ETHYL BENZENE	100-41-4	<10
n-BUTYL ALCOHOL	71-36-3	<10
TOLUENE	108-88-3	<10
XYLENE	1330-20-7	<10
ZINC OXIDE	1314-13-2	<1
ZINC PHOSPHATE	7779-90-0	<1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ETHYL BENZENE (CAS 100-41-4)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

BUTANE (CAS 106-97-8)
PROPANE (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

ACETONE (CAS 67-64-1)	6532
TOLUENE (CAS 108-88-3)	6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

ACETONE (CAS 67-64-1)	35 %WV
TOLUENE (CAS 108-88-3)	35 %WV

DEA Exempt Chemical Mixtures Code Number

ACETONE (CAS 67-64-1)	6532
TOLUENE (CAS 108-88-3)	594

US state regulations

US - California Candidate Chemicals: Listed

ACETONE (CAS 67-64-1)
AROMATIC HYDROCARBON (CAS 64742-94-5)
BUTANE (CAS 106-97-8)
TALC (CAS 14807-96-6)
TITANIUM DIOXIDE (CAS 13463-67-7)

US - California Candidate Chemicals: Listed on initial list

AROMATIC HYDROCARBON (CAS 64742-94-5)
ETHYL BENZENE (CAS 100-41-4)
TOLUENE (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

ACETONE (CAS 67-64-1)

BUTANE (CAS 106-97-8)

ETHYL BENZENE (CAS 100-41-4)

IRON OXIDE (CAS 1309-37-1)

n-BUTYL ALCOHOL (CAS 71-36-3)

PROPANE (CAS 74-98-6)

TALC (CAS 14807-96-6)

TITANIUM DIOXIDE (CAS 13463-67-7)

TOLUENE (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

ZINC OXIDE (CAS 1314-13-2)

US. New Jersey Worker and Community Right-to-Know Act

ACETONE (CAS 67-64-1)

AROMATIC HYDROCARBON (CAS 64742-94-5)

BUTANE (CAS 106-97-8)

ETHYL BENZENE (CAS 100-41-4)

IRON OXIDE (CAS 1309-37-1)

n-BUTYL ALCOHOL (CAS 71-36-3)

PROPANE (CAS 74-98-6)

TALC (CAS 14807-96-6)

TITANIUM DIOXIDE (CAS 13463-67-7)

TOLUENE (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

ZINC OXIDE (CAS 1314-13-2)

ZINC PHOSPHATE (CAS 7779-90-0)

US. Pennsylvania Worker and Community Right-to-Know Law

ACETONE (CAS 67-64-1)

BUTANE (CAS 106-97-8)

ETHYL BENZENE (CAS 100-41-4)

IRON OXIDE (CAS 1309-37-1)

n-BUTYL ALCOHOL (CAS 71-36-3)

PROPANE (CAS 74-98-6)

TALC (CAS 14807-96-6)

TITANIUM DIOXIDE (CAS 13463-67-7)

TOLUENE (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

ZINC OXIDE (CAS 1314-13-2)

US. Rhode Island RTK

ACETONE (CAS 67-64-1)

BUTANE (CAS 106-97-8)

ETHYL BENZENE (CAS 100-41-4)

n-BUTYL ALCOHOL (CAS 71-36-3)

PROPANE (CAS 74-98-6)

TOLUENE (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

ZINC OXIDE (CAS 1314-13-2)

ZINC PHOSPHATE (CAS 7779-90-0)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE (CAS 71-43-2)

Listed: February 27, 1987

CARBON BLACK (CAS 1333-86-4)

Listed: February 21, 2003

CRYSTALLINE QUARTZ SILICA (CAS 14808-60-7)

Listed: October 1, 1988

CUMENE (CAS 98-82-8)

Listed: April 6, 2010

ETHYL BENZENE (CAS 100-41-4)

Listed: June 11, 2004

FORMALDEHYDE (CAS 50-00-0)

Listed: January 1, 1988

NAPHTHALENE (CAS 91-20-3)

Listed: April 19, 2002

TITANIUM DIOXIDE (CAS 13463-67-7)

Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2)

Listed: December 26, 1997

TOLUENE (CAS 108-88-3)

Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

TOLUENE (CAS 108-88-3)

Listed: August 7, 2009

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2)

Listed: December 26, 1997

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	06-12-2016
Version #	01
HMIS® ratings	Health: 2* Flammability: 4 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 4 Instability: 0

NFPA ratings**Disclaimer**

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create any warranty, expressed or implied. It is the responsibility of the user to determine the applicability of this information and the suitability of the material or product for any particular purpose.